# Access panel for unhinging

F2 Alu-Magic System - Access panel with or without plasterboard inlay



## **Product description:**

The access panel consists of aluminium profiles, without or with plasterboard inlay (GKBI) 12.5 mm, 15 mm or 25 mm and two snap locks.


The two frames of the access panel each consist of four individual frame parts that are firmly joined together by a special welding process. From size 300 x 300 mm, the access panel is equipped with a latch. To avoid possible accidents, this must be rehung after each opening of the door leaf. The use of the access panel in the wall as well as in the ceiling area (not accessible) is possible without any problems. There is an air gap of 1.5 mm between the frame and the door leaf, which is provided with a circumferential seal. The concealed snap locks open the access panel when pressed.











### **Special designs:**


Special dimensions in any desired size can be manufactured on request.

## Special advantages of our system

- Inexpensive solution
- Short-term delivery possible
- Quick, trouble-free installation
- Sturdy aluminium frame
- Mature technology
- Flush installation in plasterboard ceilings and walls
- Paint-ready door leaf
- Can also be used for plasterboard perforated panels

Ceiling installation





All standard sizes are available for planking thicknesses of 12.5 mm, 15 mm and 25 mm. Please enquire about other planking thicknesses!

#### Locks:

The access panel can be designed with the following lock types:

Square lock with white rosette

Round cylinder lever lock with key

Profile cylinder lock with metal rosette

SD Screwdriver lock

Hexagon socket lock

Hexagon socket lock with safety pin

Of course, the screwed version or only the aluminium frame is also available!









