


Jumbo-XXL access doors

T-XXL System for wall installation



Product description:

The access door consists of aluminium profiles with 12.5 mm plasterboard inlay and snap locks.

There is an air gap of 1.5 mm between the frame and the door leaf, which is provided with a circumferential seal. The concealed snap locks open the access panel when pressed. The outer frame consists of a very stable special aluminium profile. Special hinges make it easy to open sideways.

The Jumbo-XXL access doors can be manufactured for DIN left or DIN right hinges.

For very large openings, these stable access panels can even be manufactured with 2 leaves.



Possible applications:

- Non-load-bearing internal plasterboard walls with a planking thickness of 10 mm to 25 mm
- Solid walls

Locks:

The Jumbo-XXL access door can be designed with the following lock types:

- FS** Square lock with white rosette
- Z** Round cylinder lever lock with key
- PZ** Profile cylinder lock with metal rosette



Dimensions:

These are made-to-measure products that are manufactured exactly according to the customer's specifications.

Maximum dimensions:

- Single-part: max. width 1000 mm / max. height 2000 mm
- Two-part: max. width 2000 mm / max. height 2000 mm (without centre bar!)

Special advantages of our system

- Short-term delivery possible
- Quick, trouble-free installation
- Technically mature solution
- Flush installation in plasterboard walls and solid walls
- Particularly sturdy design
- Lateral opening possible
- Suitable for oversized wall openings
- Customised system solution



FF Systems